

## PrimaCover Evapo

## Vapour-open, non-woven covering



PrimaCover Evapo is a self-adhesive and vapour-open, non-woven covering. A special membrane on the upper side allows moisture to escape and prevents the ingress of liquids. It protects coverings that are sensitive to moisture, such as ceramic tiles and wooden floors.

## Technical data (\*)



Vapour-open

For floors and stairs



Liquid-proof



Anti-slip

Composition	Upper side Carrier Adhesive	Multi-layer membrane Polyester Acrylate dispersion
Packaging	Rolls	1 m x 25 m 1 m x 50 m
Technical data	Colour Fleece thickness Film thickness	Blue 160 g/m² 25 μm
Properties	Vapour-open (70 g / m² /24 h) Liquid-proof Anti-slip Self-adhesive Shock absorbing	
Application	Especially developed for recently laid and treated floors For ceramic tiles and wooden floors Suitable for floors and stairs	
Processing	Lanes overlap by approx. 10 cm, press seams well	
Comments	Test the suitability of the product in advance. Switch off underfloor heating before use.	

We are unable to supervise the proper and therefore successful processing of the products. Therefore, we can only guarantee the quality of the products, but not of their processing. It is up to the user to check the suitability of our products for the intended purpose.

The details stated above are guideline values established in our laboratories and at external test institutes. They may deviate slightly due to variations in the testing equipment. Subject to change without notice.

\* following the respective standard

Primaverde BV Industrieweg 22a NL-5145PV Waalwijk